

CPR Life Raft

Safety for Everyone Onboard Your Aircraft



Professional Safety Equipment for Serious Aviators Since 1920.



Multiple Boarding Stations to get in Quickly



 Comes standard with four wide, stiffened rung boarding ladders for ease of boarding from any side of the raft, even wearing a life jacket.

 Whether the canopy is furled, or the arch tubes are up, you can get multiple people into the raft, fast.





When there's a need for speed

- The SWITLIK signature convertible canopy feature also allows passengers of any age to quickly get off your vessel and safely onto the raft.
- Multiple entry points reduce the need for anyone to get into the water, reducing the risk of hypothermia.

First of its Kind 5 Year Service Interval

- Helps to reduce the overall cost of life raft ownership.
- SWITLIK's patented and military proven hermetically sealed packaging system protects the raft's materials during storage.
- Compressed air inflation provides excellent cold weather inflation performance versus traditional CO2 inflation systems.
- Visible "go/no go" gauge that lets you know your raft is ready to deploy.















Compact & Stable

- Four water pockets to ensure stability in all environments.
- The Soft valise is 21" (L) x 13" (W) x 10" (H) and weighs only 39lbs. (17.6 kg.)
- The CPR is a Commercial version of the raft designed for and adopted by the US Coast Guard AUF for helicopter Missions.

SWITLIK Signature Convertible Canopy System

- 1. Comes standard with the canopy furled upon deployment, making the raft easier to board.
- 2. Once in the raft the arch tubes can be inflated by separate CO2 cylinders or manual inflation tubes.
- 3. Canopy can be partially open to provide better ventilation or fully zipped for total protection from the worst weather.
- 4. Deflating arches upon exit is best for rescue teams to make a speedy extraction.









Soft Valise Case:

Weight:	39 lb. (18.1 kg.)
Dimensions:	22" (L) x 13" (W) x 10"(H)
Material:	Nylon Cordura

Life Raft:

Buoyancy in Fresh Water:	Total: 1,114 lb. (505.3 kg)
Buoyancy in Salt Water:	Total: 1,143 lb. (518.5 kg.)
Inflated Raft Dimensions:	84.79" Width at flats (91.77" at corners)
Floor Area (Total):	20.1 sq. ft. (1.87 sq. m)
Operating Temperature Range:	-22°F to +160°F
Inflation system:	Air
Buoyancy tube fabric:	Polyurethane Coated Nylon

Standard Equipment	Part 91 Survival Kit
Hand Pump	Sponge
Repair Clamps (2)	Signal Whistle
Hank-Crank Solar Power Flashlight	Electronic Signal Flare
Sea Anchor	Water Bailer
Knife	First Aid Kit

SWITLIK SURVIVAL PRODUCTS 1325 E. STATE ST - TRENTON, NJ 08534 USA +1-609-587-3300 - INFO@SWITLIK.COM

