

OPR Life Raft

FAA TSO C70a-II 8-Man Life Raft Safety for Everyone Onboard Your Aircraft



Professional Safety Equipment for Serious Aviators Family Owned & American Made Since 1920.

www.swittk.com



Entry from the water and getting multiple people into the raft fast has never been easier.

Four wide, sturdy boarding steps and stiffened rung ladders to easily climb over the twin tubes from any side, even wearing a life jacket.

Stiff ladder rungs float, making them easy to grab.

Once you kneel on the boarding step, you can grab a strategically placed boarding strap to support you during raft entry.





First of its Kind 5 Year Service Interval*

Helps to reduce the overall cost of life raft ownership.

SWITLIK's patented and military proven hermetically sealed packaging system protects the raft's materials during storage.

Compressed air inflation provides excellent cold weather inflation performance versus traditional CO₂ inflation systems. The raft is designed to inflate in 10 seconds regardless of temperature.

Visible "go/no go" gauge that lets you know your raft is ready to deploy.











Raft comes standard with four high-capacity, rapidly deploying, weighted ballast bags





Ventilation and Visibility

The SWITLIK Signature Convertible Canopy provides four openings for improved ventilation and 360° of visibility.

High visibility raft canopy fabric, strategically located SOLAS-Grade reflective patches and an automatically activated exterior light improve the visibility of the life raft during rescue.

SWITLIK Signature Convertible Canopy System

- 1. Comes standard with the canopy furled upon deployment, making the raft easier to board.
- 2. Once in the raft the arch tubes can be inflated by separate CO2 cylinders or manual inflation tubes.
- 3. Canopy can be partially open to provide better ventilation or fully zipped for total protection from the worst weather.
- 4. Deflating arches upon exit is best for rescue teams to make a speedy extraction.











Technical Specifications

Soft Valise Case:

Weight:	FAR 91: 50 lb. (22.7 kg.)	
	FAR 135: 56 lb. (25.4 kg.)	
Dimensions:	26.5" (L) x 14" (W) x 12"(H)	
Material:	Nylon Cordura	

Life Raft:

Buoyancy in Fresh Water:	Total: 1,324 lb. (600.6 kg)	
Buoyancy in Salt Water:	Total: 1,358 lb. (616 kg.)	
Inflated Raft Dimensions:	83.98" Width at flats (90.89" at corners)	
Floor Area (Total):	24 sq. ft. (2.23 sq. m)	
Operating Temperature Range:	-22°F to +160°F	
Inflation system:	Air	
Buoyancy tube fabric:	Polyurethane Coated Nylon	



Equipment Package for 8-person Life Raft - Packed according to TSO C70a -II regulations.

LIFERAFT EQUIPMENT	FAR 91 KIT	FAR 135 KIT*
Auto Deploying Sea Anchor	Water Bailer	Fishing Kit
Heaving Ring	Electronic Signal Flare (1)	Food Rations
Inflatable Floor	Raft Repair Kit / Hand Pump	Compass
Buoyant Safety Knife	First Aid Kit	Retaining Line
Manual Inflation Pump	Hand Crank Solar Flashlight	Pyrotechnic Flare (1)
4 TSO Compliant Water Pockets	Signal Whistle	Praddles (2)
Operating Instructions	Utility Knife	Desalinator (2 Seapacks)
*	Sponge	Survival Manual

*ALSO INCLUDES ALL FAR 91 ITEMS





SWITLIK SURVIVAL PRODUCTS 1325 E. STATE ST - TRENTON, NJ 08534 USA

